



TLC-200M-U2-4K

4K USB Webcam with Microphone



A High Level e-PTZ Webcam for Desktop Conferencing

TLC-200M-U2-4K is a high level 4K Ultra HD USB2.0 webcam, no PSU requested, power/control/video from a single USB2.0 cable

Build-in dual beam forming microphones, able to pick up distance 5 meters.

Ideal option for high quality desktop video conferencing.

Features and Specification



- Adopt the most advanced image DSP and 1/2.8" 8.42MP sensor, to output 3840x2160@30 UHD resolution.
- Used high quality 12MP and 120-degree optical full glass lens, output ultra-high definition and crisp image.
- 4x digital zoom



Built-in dual beam forming microphone, pick up voice at 5meters distance



- USB2.0 output
- A single USB cable for video output, camera control and power supply directly, totally minimize cable clutter.
- Support image flip function, camera can be installed upside down.

Product SPEC

Item Number	TLC-200M-U2-4K
Sensor	1/2.8-inch high-quality, 8.42-megapixel SONY CMOS sensor
Video Format	YUY2/NV12: 1280*720@15; 1024*576@20; 640*480@30
	MJPEG: 3840*2160@30; 2560*1440@30; 1920*1080@30; 1280*720@30; 1024*576@30; 640*480@30
	H.264/H.265: 3840*2160@30; 2560*1440@30; 1920*1080@30; 1280*720@30; 1024*576@30; 640*480@30
Optical Zoom	12-megapixel fixed lens
Digital Zoom	4X
Field of Viewing	120°, distortion rate less than 4%
Sensor Resolution	8.42 megapixel
Control Port	USB2.0 (UVC1.1/UAC1.0)
Video Port	USB2.0
S/N Ratio	>50dB
Focal Length	f=2.20mm
Minimum Lux.	0.1 lux
White Balance	Auto/Manual
Iris	F=2.2
Electronic Shutter	Auto
Mirror, Flip, Anti-flicker	50HZ/60HZ/OFF
WDR	Supported
Polar distance	3~5 meters
Sensitivity	-26±2dB RL=2.2KΩ Vs=2.0V
Input Voltage	4.4~5.25V@500mA (USB port)
Dimension (L x W x H)	199mm×92.5mm×65mm
Color	Silver/Black
Net Weight	0.32KG



Telecam Technology Co.,Ltd

6 Floor, Building A, Shuanghuan Information Technology Industrial Park, No.8, Baoqing Rd, Longgang District, Shenzhen, 518116, China

Tel: +86-755-33275155

<https://www.telycam.com>